

Dedicated Convenient Printer Suits Your Business Ecology

Long-lasting and worry-less printing with New Pantum P3305 series, dedicated to easing your work with automatic duplex printing, and long-running consumables. Designed to serve SMB and enterprise workgroups environment that needs large printing quantity, Pantum P3305 series is an eco-friendly and work-smart work companion.



MONO

HIGHER CAPACITY CARTRIDGE AND STRONG METAL FRAME HELP YOU SAVE MONEY IN A LONG RUN.



One-Step Driver Installation and Direct Printing



Automatic Duplex Printing



Low Cost and Saving Money



Support AirPrint® Mopria®, Pantum App



Convenient to Print

1. Mopria, the Mopria Logo and the Mopria Alliance word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited.
2. AirPrint and the AirPrint logo are trademarks of Apple Inc.



KEY SPECIFICATIONS

P3305 Series

Monochrome Laser Printer

MODEL

■ P3305DN

■ P3305DW

PRINTING

Print technology	Mono laser	
Print speed	33ppm(A4)/35ppm(Letter)	
First print out time	Less than 8.2 seconds	
Maximum monthly duty cycle	80000 pages	
Recommended monthly volume	1000 to 10000 pages	
Processor speed	350 MHz	
Memory	256 MB	
Resolution(dpi)	1200x600	
Printer language	PCL5e, PCL6, PS3, PDF	
Duplex mode	Auto	
Control panel	2Line LCD	
NFC print	No	Yes
Network print	Yes	
Wireless print	No	Yes

PAPER HANDLING

Paper input tray	250 pages	
Multipurpose tray	1 pages	
Paper output tray	120 pages	
Media types	Plain, Thick, Transparency, Cardstock, Lable, A4, A5, JISB5, ISOB5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2, Custom	
Media sizes		
Media weight	Input tray: 60-105g/ m ² Multipurpose tray: 60-200g/ m ²	

GENERAL

Dimensions (WxDxH)	354 x334x 232mm(13.9x 13.1x9.1in)	
Weight (with toner cartridge)	6.8kg (15lb)	
Operating temperature range	10-32 °C (50-95°F)	
Operating humidity range	20% - 80% RH	
Input voltage	110V Model: AC100-127V(±10%), 50/60Hz(±2Hz), 9A 220V Model: AC220-240V(-15%, +10%), 50/60Hz(±2Hz), 4.5A	
Noise	Printing: ≤52dB(A) Standby: ≤30dB(A)	
Power consumption	Print: Average 525W Standby: 50W Dormant: Less than 2 W	
Operating system compatibility	Microsoft Windows Server2003/Server2008 Server2012/XP/Vista/Win7/Win8 Win8.1/Win10 (32/64 Bit) Mac OS 10.8-10.14 Linux: Ubuntu 14.04/16.04/18.04 (32/64 Bit)	Microsoft Windows Server2003/Server2008 Server2012/XP/Vista/Win7/Win8/Win8.1/Win10 (32/64 Bit) Mac OS 10.8-10.14 Linux: Ubuntu 14.04/16.04/18.04 (32/64 Bit) iOS 7.0 and above; Android 4.4 and above
Interface	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx Wifi: IEEE 802.11b/g/n

SUPPLIES

Cartridge style	Separate drum and toner	
Starter cartridge capacity ⁽¹⁾	TL-425 (3000 pages)	
Cartridge and drum capacity ⁽¹⁾	Cartridge: TL-425H (3000 pages, Standard); TL-425X (6000 pages, High); TL- 425U 11000 pages , Extra high)	Drum: DL-425X(25000 pages)
Starter drum unit lifetime ⁽¹⁾	DL-425X (25000 pages)	

WHAT'S IN THE BOX

Printer × 1/ 3000 Page Toner Cartridge × 1/ 25000 Page Drum unit × 1/ USB Interface Cable × 1/
Power Cord × 1/ CD-ROM × 1/ Quick Setup Guide × 1

(1) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)
Copyright © 2020 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.
*Printer data based on Pantum internal testing